



Primera AP360e and AP362e Label Applicators for Cylindrical Containers

Primera's AP-Series Label Applicators are the perfect semi-automatic labeling solution for cylindrical containers as well as many tapered containers, including bottles, cans, jars and tubes.

With an AP-Series Label Applicator you'll apply labels faster and more accurately – helping to speed up your production and sell more of your products!

Set-up and operation is fast and easy. Just:

1. Set the guides
2. Place your container in the machine
3. Press the footswitch and your label is applied

The built-in spring-loaded pressure arm makes sure labels are applied firmly and without wrinkles.



Technical Specifications

Container Width:	25.4 mm to 238 mm (1" to 9.4")
Container Diameter:	15 mm to 170 mm (0.6" to 6.7")
Container Shape:	Cylindrical and many tapered
Supply roll diameter:	Up to 203 mm (8")
Media liner width:	25.4 mm to 213 mm (1" to 8.375")
Supply roll core:	51.8 mm to 76.2 mm (2" to 3" I.D.)
Electrical rating:	12VDC, 5.0A
Power requirements:	100-240VAC, 50/60 Hz, 60 watts
Agency certifications:	UL, UL-C, CE, FCC Class A
Weight:	7.26 kg
Dimensions:	340 mmW x 226 mmH x 328 mmD
Gap between Labels:	Recommended: 3.175 mm – 6.3500 mm (1/8" – 1/4")
Label Type:	Die cut with waste removed. Clear labels can be used
Liner Thickness:	2 mil – 10 mil (smoothness will affect feeding – a liner that is too slippery or too thin will slip through the drive rollers)
Label + Adhesive Thickness:	5 mil – 15 mil *
Wind Direction:	Wound out
Manufacturer	Primera Technology Inc.

* **Important Note:** Pliability/Flexibility/Rigidity of the label is also a factor. If the label is too flexible, no matter the thickness, it can cause wrinkling or it may not pop off the liner when going around the peel edge. Polypropylene, Polyester and Vinyl labels tend to be more flexible than paper labels. If you suspect the label stock is too flexible, it is recommended that the stock and container be tested on the Applicator before making any purchase decisions of label stock or the applicator.

Apply Labels Fast and Accurately

With an AP-Series Label Applicator you'll be able to apply labels at speeds of up to 1200 per hour. Labels are perfectly applied without wrinkles, giving your finished products a highly professional look.

AP-Series Label Applicators are an ideal accessory to Primera's LX- or CX-Series label printers. The applicators can also apply roll-fed, pressure-sensitive labels produced by most other flexographic, offset and digital presses

Two Models Available



AP360e is the base model. It quickly and efficiently applies single labels at a time.



AP362e is an advanced model. It can apply one or two different labels to a single container. A built-in LED counter and memory for up to nine front-to-back label offsets is also included.

Features

- Quick set-up and easy operation
- Accurately applies labels to the front (AP360e) or front and back (AP362e) with variable spacing
- Fast – labels are applied at 135 mm (5.3") per second – up to 1200 containers per hour
- Compact size – fits on most desks and countertops
- Professionally designed – one of the only semi-automatic label applicators available with UL, CSA and FCC safety and emissions certifications
- Industrial strength – built with heavy-duty sheet metal and steel for long life

DTM Print GmbH
 Mainzer Strasse 131
 65187 Wiesbaden
 Germany
 Telefon: +49 611 92777-0
 Email: sales@dtm-print.eu
<http://dtm-print.eu>

